## delmatic metro touchpanel

The **touchpanel** provides user control and adjustment of lighting and other services via a stunning glass touchpanel user interface.

The 10" touchpanel provides high-resolution graphics while backlighting ensures images are sharp, vivid and bright. The ultra-slimline fascia appears to float against the wall and shuns the obtrusive frames seen on so many touchscreen devices.

Swipe control enables users to flip from one function to another, effortlessly controlling lights and lighting scenes, as well as other services including blinds, temperature setpoint, and integrated AV functions.

Context-sensitive graphics provide intuitive operation and a wide choice of software configurable functions. The **touchpanel** may be configured to dim or "switch off" in sleep mode yet wakes instantly upon touch activation.

The **touchpanel** connects to the Dali network and transmits user commands via the Dali network or via Lon to other interoperable building services devices.



## touchpanel

product ref: 230A1

## features

- 10" TFT LCD touchscreen
- 800 x 480 RGB resolution
- · dimmable backlighting
- fully configurable graphical screens and functions
- · automatic dim function
- automatic screen saver function
- switchable button beep
- scalable graphics
- import function of .bmp, .png, .jpg and .gif formats
- animation functions for graphical object animation.
- Dali connection
- 24V operation





The **touchpanel** is fully software configurable and can include custom graphics and logos, multiple function sub-menus as well as configuration options and user preferences.

## dimensions and mounting

	touchpanel fascia	backbox cutout
width	258 mm	212 mm
height	170 mm	146 mm
depth	10 mm (in front of wall)	70 mm (behind wall)









**London, UK** +44 (0) 20 8987 5900

delmatic@delmatic.com

**Dubai, UAE** +971 (0) 4 2566 722 sales@delmaticarabia.ae Doha, Qatar +974 4452 8226 sales@delmaticqatar.com Riyadh, Saudi Arabia +966 (0)1 211 8170 sales@delmaticsaudi.com